

Configuring Geronimo as a Windows Service

{scrollbar}

top

This article will show you how to configure Apache Geronimo v2.0 to run as a MS Windows service. A Java Service Wrapper will be required as an additional software to achieve this configuration. Using a service wrapper gives you some additional "control" on the service you are configuring such as the ability to **ping** the service and take action if the service is down.

Software prerequisites

To set up Apache Geronimo v2.0 to run as a MS Windows service you will certainly need a Java Service Wrapper. For this example we used Java Service Wrapper 3.2.3 available for download at the following URL:

<http://sourceforge.net/projects/wrapper/>

For this example we are also using Apache Geronimo v2.0 running on Windows XP. You can download Apache Geronimo binaries from the following URL:

<http://geronimo.apache.org/downloads.html>

Installing Apache Geronimo

The installation of Geronimo from the binaries is very simple. Just extract the zip file to a directory of your convenience, throughout the rest of the article this directory will be referred to as **<geronimo_home>**.

Installing the Java Service Wrapper

Installing the wrapper is as simple as installing Apache Geronimo. Once you downloaded the right version for your environment you can extract the zip file to a directory of your convenience, throughout the rest of the article this directory will be referred to as **<jsw_home>**.

For this particular example we will try to locate all the wrapper related files within the Geronimo directory structure, so we will have to copy some files over.

Once you installed the wrapper copy these as indicated in the following table.

Source	Destination
<jsw_home>/bin/wrapper.exe	<geronimo_home>/bin/wrapper.exe
<jsw_home>/lib/wrapper.jar	<geronimo_home>/lib/wrapper.jar
<jsw_home>/lib/wrapper.dll	<geronimo_home>/lib/wrapper.dll

In addition, the following files will also be created as part of this configuration process.

- <geronimo_home>/bin/g_service.bat
- <geronimo_home>/bin/Install_Geronimo_NT.bat
- <geronimo_home>/bin/Uninstall_Geronimo_NT.bat
- <geronimo_home>/var/config/wrapper.conf

Configuring the wrapper

The Java Service Wrapper comes with a sample configuration file **wrapper.conf** pre-configured to run a test script also provided, this file located in the **<jsw_home>/conf** directory. In this section we provide a Geronimo specific wrapper.conf file for your convenience.

As we are trying to keep all the wrapper files within Geronimo's directory structure, create the configuration file as illustrated in the following example and place it in the **<geronimo_home>/var/conf/wrapper.conf** directory.

```
solidwrapper.conf # Location of java.exe (in Windows) wrapper.java.command=<java_home>/bin/java # These additional parameters are required to start the server since we are not setting any environment variables prior to running the wrapper. wrapper.java.additional.1=-javaagent:<geronimo_home>/bin/jpa.jar wrapper.java.additional.2=-Djava.ext.dirs=<geronimo_home>/lib/ext;<java_home>/jre/lib/ext" wrapper.java.additional.3=-Djava.endorsed.dirs=<geronimo_home>/lib/endorsed;<java_home>/jre/lib/endorsed" wrapper.java.additional.4=-Dorg.apache.geronimo.base.dir=<geronimo_home>" wrapper.java.additional.5=-Djava.io.tmpdir=<geronimo_home>/var/temp" # Good old classpath, make sure to include /bin/server.jar and /bin/shutdown.jar wrapper.java.classpath.1=..//lib/wrapper.jar wrapper.java.classpath.2=..//bin/server.jar wrapper.java.classpath.3=..//bin/shutdown.jar wrapper.java.classpath.4=..//lib/geronimo-cliv2.0-SNAPSHOT.jar wrapper.java.classpath.5=..//lib/geronimo-kernel-v2.0-SNAPSHOT.jar wrapper.java.classpath.6=..//lib/geronimo-transformer-v2.0-SNAPSHOT.jar wrapper.java.classpath.7=..//lib/commons-cli-1.0.jar wrapper.java.classpath.8=..//lib/commons-logging-1.0.4.jar wrapper.java.classpath.9=..//lib/cglib-nodep-2.1_3.jar wrapper.java.classpath.10=..//lib/log4j-1.2.14.jar wrapper.java.classpath.11=..//lib/xpp3-1.1.3.3.jar wrapper.java.classpath.12=..//lib/xstream-1.1.3.jar # Location of the wrapper.dll (in Windows) wrapper.java.library.path.1=..//lib # Main class the wrapper will use. wrapper.java.mainclass=org.tanukisoftware.wrapper.WrapperSimpleApp # Geronimo start class and parameters. wrapper.app.parameter.1=org.apache.geronimo.cli.daemon.DaemonCLI # Log settings. wrapper.console.format=PM wrapper.console.loglevel=INFO wrapper.logfile=..//var/log/wrapper.log wrapper.logfile
```

```
format=LPTM wrapper.logfile.loglevel=INFO wrapper.logfile.maxsize=0 wrapper.logfile.maxfiles=0 wrapper.syslog.loglevel=INFO # Windows service name and description. wrapper.console.title=Apache Geronimo v2.0 Server wrapper.ntservice.name=Geronimo wrapper.ntservice.displayname=Apache Geronimo v2.0 Server wrapper.ntservice.description=Apache Geronimo v2.0 Server wrapper.ntservice.dependency.1= wrapper.ntservice.starttype=AUTO_START wrapper.ntservice.interactive=false
```

This service wrapper allows three different methods of integration depending on, among other things, whether you use the same class or not to start and stop the server.

For Geronimo we will use the simplest method of integration as the server can shutdown cleanly when `System.exit()` is called. For this integration the wrapper's mainclass is set to `WrapperSimpleApp` and the `org.apache.geronimo.cli.daemon.DaemonCLI` class is specified as the main class to start the server. Right now, no extra parameters are passed to start the server but they can be specified by adding additional `wrapper.app.parameter` values. The wrapper will stop the server by calling `System.exit()`.

As we mentioned before, for this example we are trying to locate all the wrapper related files within the Geronimo directory structure. As you can see in the `wrapper.conf` shown above, most of the directory references are relative to Geronimo's installation directory. You will only have to replace `<geronimo_home>` and `<java_home>` with the appropriate settings for your environment.

Next we will create a batch file to run the service from the command line without the need of actually installing the service. This is particularly helpful when testing and debugging the configuration. Create the `g_service.bat` batch file in the `<geronimo_home>/bin` directory and copy the content of the following example.

```
solidg_service.bat @echo off setlocal rem Copyright (c) 1999, 2006 Tanuki Software Inc. rem rem Java Service Wrapper general startup script rem rem rem Resolve the real path of the wrapper.exe rem For non NT systems, the _REALPATH and _WRAPPER_CONF values rem can be hard-coded below and the following test removed. rem if "%OS%"=="Windows_NT" goto nt echo This script only works with NT-based versions of Windows. goto :eof :nt rem rem Find the application home. rem rem %~dp0 is location of current script under NT set _REALPATH=%~dp0 rem Decide on the wrapper binary. set _WRAPPER_BASE=wrapper set _WRAPPER_EXE=%_REALPATH%_WRAPPER_BASE%windows-x86-32.exe if exist "%_WRAPPER_EXE%" goto conf set _WRAPPER_EXE=%_REALPATH%_WRAPPER_BASE%.exe if exist "%_WRAPPER_EXE%" goto conf set _WRAPPER_EXE=%_REALPATH%_WRAPPER_BASE%.exe if exist "%_WRAPPER_EXE%" goto conf echo Unable to locate a Wrapper executable using any of the following names: echo %_REALPATH%_WRAPPER_BASE%windows-x86-32.exe echo %_REALPATH%_WRAPPER_BASE%windows-x86-64.exe echo %_REALPATH%_WRAPPER_BASE%.exe pause goto :eof rem rem Find the wrapper.conf rem :conf set _WRAPPER_CONF="%~f1" if not %_WRAPPER_CONF%=="" goto startup set _WRAPPER_CONF="%_REALPATH%..\\var\\config\\wrapper.conf" rem rem Start the Wrapper rem :startup "%_WRAPPER_EXE%" -c %_WRAPPER_CONF% if not errorlevel 1 goto :eof pause
```

This file is a modified version from the one provided by the wrapper as a sample, it has been edited to specify the location of the `wrapper.conf` file relative to Geronimo's var/config directory.

You can now run Geronimo as a service from a command line, simply run the following command:

```
<geronimo_home>/bin/g_service.bat
```

You should see a screen similar to the following example, note that part has been truncated for display purposes.

Congratulations!!! you have now Geronimo server running as a Windows service.

The next step is to actually install the service so it can be picked up at Windows start time as well as managed along with the other existing services.

Installing/Removing the service

The following two batch files are provided to install and remove Geronimo as a Windows service. Create the files in the `<geronimo_home>/bin` directory and copy the content as depicted in the following examples.

```
solidInstall_Geronimo_NT.bat @echo off setlocal rem Copyright (c) 1999, 2006 Tanuki Software Inc. rem rem Java Service Wrapper general NT service install script rem if "%OS%"=="Windows_NT" goto nt echo This script only works with NT-based versions of Windows. goto :eof :nt rem rem Find the application home. rem rem %~dp0 is location of current script under NT set _REALPATH=%~dp0 rem Decide on the wrapper binary. set _WRAPPER_BASE=wrapper set _WRAPPER_EXE=%_REALPATH%_WRAPPER_BASE%windows-x86-32.exe if exist "%_WRAPPER_EXE%" goto conf set _WRAPPER_EXE=%_REALPATH%_WRAPPER_BASE%.exe if exist "%_WRAPPER_EXE%" goto conf set _WRAPPER_EXE=%_REALPATH%_WRAPPER_BASE%.exe if exist "%_WRAPPER_EXE%" goto conf echo Unable to locate a Wrapper executable using any of the following names: echo %_REALPATH%_WRAPPER_BASE%windows-x86-32.exe echo %_REALPATH%_WRAPPER_BASE%windows-x86-64.exe echo %_REALPATH%_WRAPPER_BASE%.exe pause goto :eof rem rem Find the wrapper.conf rem :conf set _WRAPPER_CONF="%~f1" if not %_WRAPPER_CONF%=="" goto startup set _WRAPPER_CONF="%_REALPATH%..\\var\\config\\wrapper.conf" rem rem Install the Wrapper as an NT service. rem :startup "%_WRAPPER_EXE%" -i %_WRAPPER_CONF% if not errorlevel 1 goto :eof pause
```

To install Apache Geronimo as a MS Windows service run the following command:

```
<geronimo_home>/bin/Install_Geronimo_NT.bat
```

You should get a confirmation screen similar to this example.

```
solidUninstall_Geronimo_NT.bat @echo off setlocal rem Copyright (c) 1999, 2006 Tanuki Software Inc. rem rem Java Service Wrapper general NT service  
uninstall script rem if "%OS%"=="Windows_NT" goto nt echo This script only works with NT-based versions of Windows. goto :eof :nt rem rem Find the  
application home. rem rem %~dp0 is location of current script under NT set _REALPATH=%~dp0 rem Decide on the wrapper binary. set  
_WRAPPER_BASE=wrapper set _WRAPPER_EXE=%_REALPATH%_WRAPPER_BASE%windows-x86-32.exe if exist "%_WRAPPER_EXE%" goto conf  
conf set _WRAPPER_EXE=%_REALPATH%_WRAPPER_BASE%windows-x86-64.exe if exist "%_WRAPPER_EXE%" goto conf echo Unable to locate a Wrapper executable  
using any of the following names: echo %_REALPATH%_WRAPPER_BASE%windows-x86-32.exe echo %_REALPATH%_WRAPPER_BASE%  
windows-x86-64.exe echo %_REALPATH%_WRAPPER_BASE%.exe pause goto :eof rem rem Find the wrapper.conf rem :conf set  
_WRAPPER_CONF="%~f1" if not %_WRAPPER_CONF%=="" goto startup set _WRAPPER_CONF="%_REALPATH%..\\var\\config\\wrapper.conf" rem  
rem Uninstall the Wrapper as an NT service. rem :startup "%_WRAPPER_EXE%" -r %_WRAPPER_CONF% if not errorlevel 1 goto :eof pause
```

To remove the Apache Geronimo service run the following command:

```
<geronimo_home>/bin/Uninstall_Geronimo_NT.bat
```

You should get a confirmation screen similar to this example.