

Apache Traffic Server

Lua Scriptlets

Leif Hedstrom
zwoop@apache.org

Example (current)

```
map http://cdn.example.com \
http://cdn.example.com \
@plugin=regex_remap.so @pparam=strip_query.config \
@plugin=header_rewrite.so @pparam=cdn_hdrs.config \
@plugin=conf_remap.so @pparam=proxy.config.url_remap.pristine_host_hdr=0 \
@action=deny @method=POST @method=PUT @method=DELETE
```

```
# strip_query.config:
. http://$t/$P
```

Example (current)

```
cond %{REMAP_PSEUDO_HOOK}
  set-header @Service "cdn"
```

```
cond %{READ_RESPONSE_HDR_HOOK}
cond %{STATUS} >199 [AND]
cond %{STATUS} <299
rm-header Pragma
rm-header Expires
set-header Cache-Control "max-age=2592000, public"
```

New remap.config

```
map http://cdn.example.com http://cdn.example.com @lua=cdn.lua
```

```
local TS = require 'ts'
DENY_METHODS = { 'POST', 'PUT', 'DELETE' }

function remap(request)
    TS.set_config('proxy.config.url_remap.pristine_host_hdr', 0)
    request.headers['@Service'] = 'cdn'

    url = request:url()
    url.query = ''

    if DENY_METHODS[request.method()] ~= nil # can do more here!
        return false
    else
        return true
    end

function read_response_header(request, response)
    url = request:url()

    if response.status() < 199 and response.status() > 299 then
        response.headers['Pragma'] = nil
        response.headers['Expires'] = nil
        response.headers['Cache-Control'] = 'max-age=2592000, public'
    end
end
```

Many callbacks

```
local TS = require 'ts'

function parent_selection(request)
    url = request:url()
    if url... then
        return 'cdn-parent1.example.com'
    else
        return cdn-parent2.example.com'
    end
end
```