### What's New In v4.2.x

A brief summary for Users and Administrators (the Jira's are active links) v4.2.x is a Long Term Support release (LTS)

### New Features

- [TS-32] We now support ICP again, the old configurations are now functional
- [TS-312] Keep-Alive connections to origin are now always shared. The old behavior can be restored via a new configuration
- [TS-2350] The traffic\_top tool adds a number of new features, such as showing multiple stats pages.
- [TS-2483] Add cache 'status/readiness' metric to trafficserver, this lets you see when the cache became available (and hence, you can see how long it took to initialize).
- [TS-2487] export PUSH method API constants
- [TS-2533] Add alarms and status information / mgmt to traffic\_line
- [TS-2541] We can now proxy WebSockets, configured via normal remap.config (e.g. map <u>ws://www.example.com</u> <u>ws://ws.example.com:9090</u>)

### New Features - SSL

- [TS-1146] RFC 5077 TLS Session tickets
- [TS-1668] We now support HSTS via new configurations, overridable per remap rule
- [TS-2365] Configure max TLS record size
- [TS-2372] Add forward secrecy support for SSL
- [TS-2413] Release memory for idle SSL connection
- [TS-2416] Configurable TLS session timeout threshold

# New Features - Plugins

- [TS-2117] New plugin donated by Yahoo, HiPES (see its documentation)
- [TS-2335] A new, more complete Lua plugin is available in the experimental/ build
- [TS-2426] xdebug plugin for debugging headers using client directives
- [TS-2316] header\_rewrite plugin now supports various variable expansions for values
- [TS-2361] Load regex\_remap plugin configurations relative to main config directory
- [TS-2544] conf\_remap plugin now allow for multiple configuration files
- [TS-2550] conf\_remap can take configuration arguments directly in remap.config

## New Features -APIs

- [TS-2271] Threaded plugin support with 3rd party libraries
- [TS-2336] Move InkAPIHughes.h (Prefetch APIs) into experimental.h. These APIs allows for some control over the Prefetching feature (parsing HTML and prefetch page components).
- [TS-2484] Missing API (ts/ts.h) support for a few overridable configurations

## New Features - Logs / Docs

- [TS-2364] Introduce slice notation to field syntax in log format. This allows for controlled truncation of fields that can be very long
- [TS-2379] Add a new field: '%<chp>',
  "client\_host\_port" to LogFormat
- [TS-2377] DOC: install man pages as part of the build

# Improvements

- [TS-2077] Remove pipelining configuration remnants (proxy.config.http.user\_agent\_pipeline). These configurations had no purpose
- [TS-2343] Remove the --schema option from Traffic Manager
- [TS-2348] rename tstop to traffic\_top for consistency
- [TS-2370] SSL cipher order was backwards (proxy.config.ssl.server.honor\_cipher\_order)
- Stability improved