

property

Please make sure you have read the [Tag Syntax](#) document and understand how tag attribute syntax works.

Description

Used to get the property of a *value*, which will default to the top of the stack if none is specified.

Parameters

Dynamic Attributes Allowed:

false

Name	Required	Default	Evaluated Type	Description
default	false		String	The default value to be used if <i>value</i> attribute is null
escapeCsv	false	false	Boolean	Whether to escape CSV (useful to escape a value for a column)
escapeHtml	false	true	Boolean	Whether to escape HTML
escapeJavaScript	false	false	Boolean	Whether to escape Javascript
escapeXml	false	false	Boolean	Whether to escape XML
value	false	<top of stack>	Object	Value to be displayed

Examples

Error rendering macro 'code': Invalid value specified for parameter 'java.lang.NullPointerException'

```
<s:push value="myBean">
  <!-- Example 1: -->
  <s:property value="myBeanProperty" />

  <!-- Example 2: -->TextUtils
  <s:property value="myBeanProperty" default="a default value" />
</s:push>
```

Error rendering macro 'code': Invalid value specified for parameter 'java.lang.NullPointerException'

Example 1 prints the result of myBean's getMyBeanProperty() method.
Example 2 prints the result of myBean's getMyBeanProperty() method and if it is null, print 'a default value' instead.