

# 1.1.2.5. JMS

JMS Console Navigation JMS Server JMS Network Listener JMS Server JMS Server Manager JMS2

JMS Server Manager

help [view]

The JMS brokers available in the server are:

| Name     | State   |
|----------|---------|
| ActiveMQ | running |

JMS Network Listeners

help [view]

Currently available JMS network connectors:

| Name                   | Broker   | Protocol | Port  | State   | Actions                                                          |
|------------------------|----------|----------|-------|---------|------------------------------------------------------------------|
| ActiveMQ.stomp.default | ActiveMQ | stomp    | 61613 | running | <a href="#">stop</a> <a href="#">edit</a> <a href="#">delete</a> |
| ActiveMQ.tcp.default   | ActiveMQ | tcp      | 61616 | running | <a href="#">stop</a> <a href="#">edit</a> <a href="#">delete</a> |

Add connector to ActiveMQ:

- ◆ [Add new tcp listener](#)
- ◆ [Add new stomp listener](#)
- ◆ [Add new vm listener](#)
- ◆ [Add new peer listener](#)
- ◆ [Add new udp listener](#)
- ◆ [Add new multicast listener](#)
- ◆ [Add new failover listener](#)

JMS Network Listeners (stop,start,delete)ActiveMQ

ActiveMQ Save

JMS Network Listeners

help [view]

Add new tcp connector for ActiveMQ

Unique Name:

A name that is different than the name for any other JMS connectors in the server

Host:

The host name or IP to bind to. The normal values are 0.0.0.0 (all interfaces) or localhost (local connections only)

Port:

The network port to bind to.

SaveReset

[List JMS connectors](#)

(destination) [1.1.4.3. JMS](#)