

Using Camel Questions

Questions on using Apache Camel

- [ClassLoader issue of servicemix-camel component](#)
- [How do I specify which method to use when using beans in routes?](#)
- [How can I create a custom component or endpoint](#)
- [How can I get the remote connection IP address from the camel-cxf consumer ?](#)
- [How can I stop a route from a route](#)
- [How can webservice clients see remote faults with stacktraces when using camel-cxf](#)
- [How does Camel look up beans and endpoints](#)
- [How do I add a component](#)
- [How do I change the logging](#)
- [How Do I Configure Endpoints?](#)
- [How do I configure password options on Camel endpoints without the value being encoded](#)
- [How do I configure the default maximum cache size for ProducerCache or ProducerTemplate](#)
- [How do I configure the maximum endpoint cache size for CamelContext](#)
- [How do I debug my route](#)
- [How do I disable JMX](#)
- [How do I enable streams when debug logging messages in Camel](#)
- [How do I handle failures when consuming for example from a FTP server](#)
- [How do I import rests from other XML files](#)
- [How Do I Import Routes From Other XML Files?](#)
- [How do I let Jetty match wildcards](#)
- [How do I name my routes?](#)
- [How do I restart CamelContext](#)
- [How do I retrieve the thrown Exception during processing an Exchange](#)
- [How do I retry failed messages forever](#)
- [How do I retry processing a message from a certain point back or an entire route](#)
- [How do I reuse the ContextTestSupport class in my unit tests](#)
- [How do I run ActiveMQ and Camel in JBoss](#)
- [How do I set the max chars when debug logging messages in Camel](#)
- [How do I specify time period in a human friendly syntax](#)
- [How do I use a big \(uber\) JAR?](#)
- [How do I use Camel inside ServiceMix](#)
- [How do I use Spring Property Placeholder with Camel XML](#)
- [How do I use URIs with parameters in XML](#)
- [How do I write a custom Processor which sends multiple messages](#)
- [How should I invoke my POJOs or Spring Services](#)
- [How should I package applications using Camel and ActiveMQ](#)
- [How to avoid importing bunch of cxf packages when start up the camel-cxf endpoint from OSGi platform ?](#)
- [How to avoid sending some or all message headers](#)
- [How to define a static camel converter method in Scala](#)
- [How to remove the http protocol headers in the camel message?](#)
- [How to send the same message to multiple endpoints](#)
- [How to switch the CXF consumer between HTTP and HTTPS without touching the Spring configuration](#)
- [How to use a dynamic URI in to\(\)](#)
- [How to use extra camel componets in servicemix-camel](#)
- [How to validate the camel-1.x context xml from Apache Camel web site?](#)
- [Is there an IDE](#)
- [Should I deploy Camel inside the ActiveMQ broker or in another application](#)
- [Using camel-core-tests.jar](#)
- [Using getIn or getOut methods on Exchange](#)
- [Why can't I use + sign in my password](#)
- [Why can I not use when or otherwise in a Java Camel route](#)
- [Why does FTP component not download any files?](#)
- [Why does my file consumer not pick up the file, and how do I let the file consumer use the Camel error handler?](#)
- [Why does useOriginalMessage with error handler not work as expected?](#)
- [Why do my message lose its headers during routing?](#)
- [Why is my message body empty?](#)
- [Why is my processor not showing up in JConsole](#)
- [Why is the exception null when I use onException](#)
- [Why use multiple CamelContext](#)