

OpenID Connect OSGI Configuration File

Activities Firefox Web Browser Apache Sling Web Console - Configuration - Mozilla Firefox (Private Browsing)

localhost:8080/oidc/config x Apache Sling Web Console x +

localhost:8080/system/console/configMgr

Apache Sling Scripting HTML JavaScript Use-API Factories Configuration -

Apache Sling Scripting Resource Resolver Provider Configuration -

Apache Sling Service User Mapper Service -

Apache Sling Service User Mapper Service Amendment -

Mapping: org.apache.sling.cacore.config.impl.sling-readall -

Mapping: org.apache.sling.discovery.commons.sling-discovery, org.apache.sling.discovery.base.sling-discovery, org.apache.sling.discovery.oak.sling-discovery -

Mapping: org.apache.sling.event.sling-event, org.apache.sling.event.de.sling-event -

Mapping: org.apache.sling.idm.sling-idm -

Mapping: org.apache.sling.installer.provider.js.sling-js-install -

Mapping: org.apache.sling.js.resource.observation.sling-readall -

Mapping: org.apache.sling.js.resource.validation.sling-readall -

OpenID Connect Configuration

Enable ☐

Enable OpenID Connect Authentication Handler (servicename.enable.boolean)

OpenID Connect Provider

Select a Provider (servicename.provider.dropdown)

Client ID

Enter Client ID (servicename.clientid.string)

Client Secret

Enter Client Secret (servicename.clientsecret.password)

Configuration Information

Persistent Identity (PID)

Configuration Binding

Cancel Reset Delete Unbind Save

Component Apache Sling Health Check Result HTML Serializer -

Composum Core Client Configuration -

Composum Core Configuration -

Composum Filter Configuration -

Composum Nodes (Console) Configuration -

Composum PackageService -

Groovy Job Executor Service -

Oak Segment Tar NodeStore service -

OpenID Connect Configuration -

Package Job Executor Service -